



FWC LED

BWC110 LED9-/830 PSU II WH PH

BWC110 | SECURITY LED 110, LED9 | LED Module 900 lm, Power supply unit (On/Off), Photocell included

Feel safe with this energy-efficient wall mounted security luminaire. The LED arrangement and housing cover produce excellent light distribution for lower lighting levels for walls, corridors and the surrounding area.

Product data

General Information	
Lamp family code	LED9 [LED Module 900 lm]
Light source replaceable	Yes
Number of gear units	1 unit
Driver included	Yes
Light source engine type	LED
Service tag	Yes
Lighting Technology	LED
Value ladder	Value
Serviceability class	Class C, luminaire without serviceable parts, not serviceable
Warranty period	5 years
Sustainability rating	-
Light Technical	
Upward light output ratio	0.08
Luminous Flux	900 lm
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	100 lm/W
Color rendering index (CRI)	80

Number of light sources	1
Beam angle of light source	120 degree(s)
Light source color	830 warm white
Optic type	-
Luminaire light beam spread	180°
Optic type outdoor	Symmetrical
Effective projected area	0.04 m²
Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Inrush current	27 A
Inrush time	0.25 ms
Power Consumption	9 W
Power Factor (Fraction)	0.95
Connection	Screw connection block 3-pole
Cable	-
Number of products on MCB of 16 A type B	50
Protection class IEC	Safety class II
Surge Protection (Common/Differential)	Standard surge protection level

Total harmonic distortion	20 %
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No
Photocell	Photocell included
Mechanical and Housing	
Housing Material	Acrylonitrile styrene acrylate
Reflector material	-
Optic material	-
Optical cover material	UV stabilized Polycarbonate cover
Fixation material	Polyamide
Housing Color	White
Mounting device	Wall-mounting bracket
Optical cover shape	Curved
Optical cover finish	Opal
Overall length	242 mm
Overall width	242 mm
Overall height	136 mm
Dimensions (Height x Width x Depth)	136 x 242 x 242 mm
Ingress protection code	IP54 [Dust accumulation-protected, splash-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Standard tilt angle posttop	0°
Standard tilt angle side entry	0°
Optical cover type	Opal bowl/cover
Net Weight (Piece)	0.850 kg
Approval and Application	
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	ENEC mark

EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Remarks	* At extreme ambient temperatures the luminaire might automatically dim down to protect components
Ambient temperature range	-40 to +50 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.43, 0.40) SDCM <3
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤3
Over Time Performance (IEC Compliant)	
Driver failure rate at 5000 h	1 %
Control gear failure rate at median useful life 50000 h	20 %
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	L80
Product Data	
Order product name	BWC110 LED9-/830 PSU II WH PH
Full product name	BWC110 LED9-/830 PSU II WH PH
Full product code	871829185190599
Order code	910500454098
Material Nr. (12NC)	910500454098
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718291851905
Numerator - Packs per outer box	4
EAN/UPC - Case	8718291851981
Product family code	BWC110 [SECURITY LED 110]

Dimensional drawing



