



Ledinaire Waterproof WT065C

WT065C LED29_48S/840 PSU L1200

Ledinaire Waterproof WT065C, All-in, 42 W, 23 W, L1200 mm, 2900 lm, 4800 lm, 4000 K, Symmetrical, Opal, IP65, IK08, TW1-ready

The Ledinaire Waterproof range provides maximum performance and durability at great value. As an off-the-shelf LED luminaire solution for all your everyday needs, it can be deployed in a wide variety of locations.

Product data

General Information	
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Service tag	No
Lighting Technology	LED
Value ladder	Value
Serviceability class	Class C, luminaire without serviceable
	parts, not serviceable
Mamanturaniad	2
Warranty period	3 years
Sustainability rating	s years
	s years
	o years
Sustainability rating	2,900 4,800 lm
Sustainability rating Light Technical	-
Sustainability rating Light Technical Luminous Flux	2,900 4,800 lm

Luminous Efficacy (rated) (Nom)	126 114 lm/W
Color rendering index (CRI)	>80
Light source color	840 neutral white
Optic type	Symmetrical
Luminaire light beam spread	110°
Unified glare rating CEN	31
All-in Type	All-in, Multi Lumen
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Inrush current	14.2 A
Inrush time	0.222 ms
Power Consumption	42 23 W
Power Factor (Fraction)	0.9
Connection	Push-in connector 3-pole

Datasheet, 2025, April 29 data subject to change

Ledinaire Waterproof WT065C

Cable	
Number of products on MCB of 16 A type B	36
Suitable for random switching	No
Protection class IEC	Safety class I
Feed-through wiring	Simple Connection and removable cover
	available for feed-through wiring 1-
	phase (internal wiring is not included)
Total harmonic distortion	12 %
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	
Constant light output	No
Mechanical and Housing	
Housing Material	Polycarbonate
Reflector material	Steel
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Stainless steel
Housing Color	Grey
Optical cover finish	Opal
Overall length	1,207 mm
Overall width	71 mm
Overall height	74 mm
Dimensions (Height x Width x Depth)	74 x 71 x 1207 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-
	proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Net Weight (Piece)	1.150 kg
Emangangu Onavati	
Emergency Operation	
Central Emergency	No
Approval and Application	
Glow-wire test	Temperature 850 °C, duration 30 s
Flammability mark	For mounting on easily flammable
	surfaces

CE mark	Yes
ENEC mark	-
Photobiological risk	Photobiological risk group 1 @200mm to
	EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Flickering value (PstLM) - Flickering value as	1
per EN 61000-3-3	
Stroboscopic effect visibility measure (SVM)	0.4
Ambient temperature range	−20 to +40 °C
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38,0.38) SDCM≤5
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching	SDCM≤5
(McAdam ellipse)	
Over Time Performance (IEC Compliant	·)
Control gear failure rate at median useful life	7.5 %
50000 h	
Lumen maintenance (EN-IEC 62722-2-1) at	L70
median useful life* 50000 h	
Lumen maintenance (EN-IEC 62722-2-1) at	-
median useful life* 75000 h	
Product Data	
Order product name	WT065C LED29_48S/840 PSU L1200
Full product name	WT065C LED29_48S/840 PSU L1200
Full product code	872016950021199
Order code	911401815185
Material Nr. (12NC)	911401815185
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169500211
Numerator - Packs per outer box	9
EAN/UPC - Case	8720169500310

Ledinaire Waterproof WT065C

Dimensional drawing





© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.