



Power	150 W	Voltage	230 V
Luminous flux*	23000 lm (360°)	Colour temperature	4000 K
Light colour	Neutral white	Beam angle	90 °
UGR	n/a	IK	10





 User manual



 Photometric file

Technical data:

Product code	SLI048002NW_PW
Power	150 W
Nominal current	670 mA
Voltage	230 V
Energy efficiency classe	D
Energy consumption	150 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.95
Useful luminous flux*	23000 lm (360°)
Luminous flux**	21000 lm (360°)
Light efficiency	153 lm/W
Luminous intensity	11000 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	90 °
UGR	n/a
RA	>80
Light source included	Yes
Dimmable	+
Working temperature range	-20 +40 °
Lifespan	50000 h
Housing material	Aluminum
IK	10
Protection class	IP66
Colour	Black
Dimension (axbxc)	745x126x95 mm
For use	Outside/Inside
Assembly method	Suspended
Whether it should work in conditions other than normal?	Yes
Made in	PRC



*Applies to the LED source used. **Luminaire luminous flux
The set includes 2 slings with a length of 1 meter.