


IP54 117  
lm/W



Power **24 W**  
Luminous flux\* **2800 lm (360°)**  
Light colour **WW**  
IK **04**

Voltage **230 V**  
Colour temperature **3000 K**  
Beam angle **115 °**  
Protection class **IP54**



 User manual




 Declaration of Conformity



 Photometric file

#### Technical data:

|                              |                   |
|------------------------------|-------------------|
| Product code                 | SLI031035WW_PW    |
| Power                        | 24 W              |
| Nominal current              | 175 mA            |
| Voltage                      | 230 V             |
| Energy efficiency classe     | E                 |
| Energy consumption           | 24 kWh/1000h      |
| Frequency                    | 50HZ Hz           |
| Protection class             | II                |
| Power supply included        | +                 |
| Power factor                 | 0.6               |
| Useful luminous flux*        | 2800 lm (360°)    |
| Luminous flux**              | 1650 lm (360°)    |
| Light efficiency             | 117 lm/W          |
| Luminous intensity           | 1050 cd           |
| Colour temperature           | 3000 K            |
| Light colour                 | WW                |
| Beam angle                   | 115 °             |
| RA                           | >80               |
| Light source included        | +                 |
| Uniformity of color SDCM max | 5                 |
| Dimmable                     | -                 |
| Working temperature range    | -20 +40 °         |
| Lifespan                     | 17000 h           |
| Housing material             | TWORZYWO SZTUCZNE |
| IK                           | 04                |
| Protection class             | IP54              |
| Colour                       | White             |
| Dimension (axbxc)            | Ø 320 x 52 mm     |
| For use                      | Inside/Outside    |
| Assembly method              | On the ceiling    |
| Application                  | Inside/Outside    |
| Made in                      | PRC               |



\*Applies to the LED source used. \*\*Luminaire luminous flux