



|                  |                      |                    |               |
|------------------|----------------------|--------------------|---------------|
| Power            | <b>36 W</b>          | Voltage            | <b>24 V</b>   |
| Luminous flux*   | <b>2000 lm (90°)</b> | Colour temperature | <b>3000 K</b> |
| Light colour     | <b>WW</b>            | Beam angle         | <b>45 °</b>   |
| Protection class | <b>IP65</b>          |                    |               |



 Declaration of Conformity



 Photometric file

#### Technical data:

|                              |                |
|------------------------------|----------------|
| Product code                 | SLI001013WW    |
| Power                        | 36 W           |
| Nominal current              | 1500 mA        |
| Voltage                      | 24 V           |
| Energy efficiency classe     | G              |
| Energy consumption           | 40 kWh/1000h   |
| Frequency                    | DC Hz          |
| Protection class             | III            |
| Power supply included        | -              |
| Power factor                 | 1              |
| Useful luminous flux*        | 2000 lm (90°)  |
| Luminous flux**              | 2000 lm (360°) |
| Light efficiency             | 55 lm/W        |
| Colour temperature           | 3000 K         |
| Light colour                 | WW             |
| Beam angle                   | 45 °           |
| Light source included        | +              |
| Uniformity of color SDCM max | 6              |
| Dimmable                     | +              |
| Working temperature range    | -20/+40 °      |
| Lifespan                     | 50000 h        |
| Housing material             | Aluminum       |
| Protection class             | IP65           |
| Colour                       | Gray           |
| Dimension (axbxc)            | 1000x43x85 mm  |
| For use                      | Inside/Outside |
| Assembly method              | On the ceiling |
| Application                  | INT/EXT        |
| Made in                      | PRC            |



\*Applies to the LED source used. \*\*Luminaire luminous flux  
\*Light colour 4000 K available on request. Requires 24V power supply.