

IP65 130
lm/W



Power	45 W	Voltage	230 V
Luminous flux*	5400 lm (120°)	Colour temperature	4000 K
Light colour	Neutral white	Beam angle	120 °
Protection class	IP65		




 User manual



 Declaration of Conformity

Technical data:

Product code	SLI028031NW_PW
Power	45 W
Nominal current	200 mA
Voltage	230 V
Energy efficiency classe	E
Energy consumption	45 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.98
Useful luminous flux*	5400 lm (120°)
Luminous flux**	5150 lm (360°)
Light efficiency	120 lm/W
Luminous intensity	1550 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
RA	>80
Light source included	Yes
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	plastic
Protection class	IP65
Colour	White
Dimension (axbxc)	1680 x 52 x 27 mm
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	Inside/Outside
Made in	PRC
Other	dane na moduł FI use=5400 P=45W ,



*Applies to the LED source used, **Luminaire luminous flux