

153  
lm/W



|                |                       |                    |               |
|----------------|-----------------------|--------------------|---------------|
| Power          | <b>32 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux* | <b>4900 lm (360°)</b> | Colour temperature | <b>3000 K</b> |
| Light colour   | <b>WW</b>             | Beam angle         | <b>120 °</b>  |
| IK             | <b>06</b>             | Protection class   | <b>IP20</b>   |



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

|                              |                          |
|------------------------------|--------------------------|
| Product code                 | SLI045002WW_PW           |
| Power                        | 32 W                     |
| Nominal current              | 140 mA                   |
| Voltage                      | 230 V                    |
| Energy efficiency classe     | D                        |
| Energy consumption           | 32 kWh/1000h             |
| Frequency                    | 50HZ Hz                  |
| Protection class             | II                       |
| Power supply included        | +                        |
| Power factor                 | 0.9                      |
| Useful luminous flux*        | 4900 lm (360°)           |
| Luminous flux**              | 4000 lm (360°)           |
| Light efficiency             | 153 lm/W                 |
| Colour temperature           | 3000 K                   |
| Light colour                 | WW                       |
| Beam angle                   | 120 °                    |
| RA                           | 80                       |
| Uniformity of color SDCM max | 5                        |
| Dimmable                     | -                        |
| Working temperature range    | -20/+40 °                |
| Lifespan                     | 17000 h                  |
| Housing material             | PC                       |
| IK                           | 06                       |
| Protection class             | IP20                     |
| Colour                       | White                    |
| Dimension (axbxc)            | 76x1200x26 mm            |
| For use                      | Inside                   |
| Assembly method              | On the ceiling/Suspended |
| Application                  | INT                      |
| Made in                      | PRC                      |



\*Applies to the LED source used, \*\*Luminaire luminous flux