

# PRODUCT DATASHEET

## ENDURA STYLE UpDown Puck 13 W DG

ENDURA® STYLE UPDOWN PUCK | Luminaire with direct up and down light output



---

### Areas of application

- Outdoor use (IP44)
- Building facades
- Entrance lighting
- Patios, balconies

---

### Product benefits

- Easy and quick installation
- Energy-efficient thanks to LED technology

---

### Product features

- Bright and functional outdoor LED luminaires
- Die-cast aluminum housing
- Available in two housing colors



## TECHNICAL DATA

### Electrical data


|                        |                               |
|------------------------|-------------------------------|
| Nominal wattage        | 12.50 W                       |
| Nominal voltage        | 220...240 V                   |
| Mains frequency        | 50...60 Hz                    |
| Nominal current        | 85 mA                         |
| Power factor $\lambda$ | > 0.5                         |
| Protection class       | I                             |
| Operating mode         | Electronic control gear (ECG) |

### Photometrical data

|                                      |            |
|--------------------------------------|------------|
| Luminous flux                        | 980 lm     |
| Luminous efficacy                    | 75 lm/W    |
| Color temperature                    | 3000 K     |
| Light color (designation)            | Warm White |
| Color rendering index Ra             | $\geq 80$  |
| Standard deviation of color matching | < 6 sdcm   |
| Beam angle                           | 110 °      |

### Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 131.00 mm |
| Width          | 91.00 mm  |
| Height         | 110.00 mm |
| Product weight | 630.00 g  |



### Materials & Colors

|               |           |
|---------------|-----------|
| Product color | Dark gray |
| Housing color | Dark gray |
| Body material | Aluminum  |

|                |                               |
|----------------|-------------------------------|
| Cover material | Polymethylmethacrylate (PMMA) |
|----------------|-------------------------------|

### Application & Mounting

|                              |                 |
|------------------------------|-----------------|
| Ambient temperature range    | -20...+40 °C    |
| Temperature range at storage | -30...+70 °C    |
| Type of connection           | Screw terminal  |
| Type of protection           | IP44            |
| Dimmable                     | No              |
| Mounting type                | Surface         |
| Mounting location            | Wall            |
| LED module replaceable       | Not replaceable |

### Lifespan

|                            |         |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C  | 50000 h |
| Number of switching cycles | 15000   |

### Certificates & Standards

|           |                         |
|-----------|-------------------------|
| Standards | CE / EAC / REACH / RoHS |
|-----------|-------------------------|

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

### DOWNLOAD DATA

| DOWNLOAD DATA                                                                       |                                                            |
|-------------------------------------------------------------------------------------|------------------------------------------------------------|
|   | User instruction<br>ENDURA STYLE UPDOWN PUCK 13W           |
|  | Tender documents<br>Tender Text 4058075205567              |
|   | Declarations of conformity<br>ENDURA STYLE MIDI and UPDOWN |
|   | Packaging insert<br>Legal Insert B - Outdoor Not dimmable  |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075205567 | Folding box<br>1             | 124 mm x 154 mm x 166 mm             | 670.00 g     | 3.17 dm <sup>3</sup>  |
| 4058075205574 | Shipping box<br>6            | 385 mm x 170 mm x 355 mm             | 4252.00 g    | 23.23 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.