

IP44



Power **30 W**  
Luminous flux\* **2800 lm (120°)**  
Light colour **Neutral white**  
IK **07**

Voltage **230 V**  
Colour temperature **4000 K**  
Beam angle **100 °**  
Protection class **IP44**





 Declaration of Conformity



 Photometric file

**Technical data:**

|                              |                        |
|------------------------------|------------------------|
| Product code                 | SLI029050NW_CZUJNIK_PW |
| Power                        | 30 W                   |
| Nominal current              | 130 mA                 |
| Voltage                      | 230 V                  |
| Energy efficiency classe     | F                      |
| Energy consumption           | 30 kWh/1000h           |
| Frequency                    | 50HZ Hz                |
| Protection class             | I                      |
| Power supply included        | +                      |
| Power factor                 | 0.9                    |
| Useful luminous flux*        | 2800 lm (120°)         |
| Luminous flux**              | 2800 lm (360°)         |
| Light efficiency             | 93 lm/W                |
| Colour temperature           | 4000 K                 |
| Light colour                 | Neutral white          |
| Beam angle                   | 100 °                  |
| RA                           | >70                    |
| Uniformity of color SDCM max | 5                      |
| Dimmable                     | -                      |
| Working temperature range    | -20/+40 °              |
| Lifespan                     | 17000 h                |
| Housing material             | Aluminum, GLASS        |
| IK                           | 07                     |
| Protection class             | IP44                   |
| Colour                       | Black                  |
| Dimension (axbxc)            | 150x190x53 mm          |
| For use                      | Outside                |
| Assembly method              | On the ceiling         |
| Application                  | EXT                    |
| Made in                      | PRC                    |



\*Applies to the LED source used. \*\*Luminaire luminous flux