

100
lm/W



Power **18 W**
Luminous flux* **1800 lm (120°)**
Light colour **WW**
IK **06**

Voltage **230 V**
Colour temperature **3000 K**
Beam angle **110 °**
Protection class **IP20**



 User manual



 Declaration of Conformity



 Photometric file



Technical data:

Product code	SLI037029WW
Power	18 W
Nominal current	134 mA
Voltage	230 V
Energy efficiency classe	E
Energy consumption	18 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.5
Useful luminous flux*	1800 lm (120°)
Luminous flux**	1800 lm (360°)
Light efficiency	100 lm/W
Luminous intensity	670 cd
Colour temperature	3000 K
Light colour	WW
Beam angle	110 °
RA	>80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	PLASTIC
IK	06
Protection class	IP20
Colour	White
Dimension (axbxc)	223x35 mm
Mounting hole	ø200 mm
For use	Inside
Assembly method	surface mounted, recessed
Application	Inside
Made in	PRC



*Applies to the LED source used. **Luminaire luminous flux