

SLI035050NW_BLACK_PW


SLI035050NW_BLACK_PW



Power	44 W	Voltage	230 V
Luminous flux*	5700 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	70 °
UGR	<16	IK	06

Technical data

Code	SLI035050NW_BLACK_PW
Power	44 W
Nominal current	200 mA
Voltage	230 V
Energy consumption	44 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	SPECTRUM
Power factor	0.9
Useful luminous flux*	5700 lm (360°)
Luminous flux**	5300 lm (360°)
Lamp efficacy	130 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	70 °
UGR	<16
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	STAL
IK	06
Degree of protection (IP)	IP20
Colour	Black
Dimension (AxBxC)	597x597x40 mm
Mounting hole	565X565 mm
For use	Inside
Assembly method	Recessed, On the ceiling, Suspended
Application	INT
Made in	PRC



Related documents



 User manual



 Declaration of Conformity



 Photometric file

