

ALGINE BACKLIGHT CCT

SLI035073CCT_PW

LED luminaire ALGINE BACKLIGHT CCT with the possibility of changing the light color (CCT), with power regulation on the power supply (30/40/48 W), high light efficacy 131 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 3000/4000/6000K, we can adjust the light color depending on our needs and preferences. It is made of high-quality components, supported by a 5-year warranty. The CCT function allows you to changes to the colour temperature of light (3000/4000/6000K). Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	30/40/48 W	Voltage	230 V
Luminous flux*	6300 lm (360°)	Colour temperature	3000/4000/6000 K
Colour of light	CCT	Beam angle	120 °
Degree of protection (IP)	IP20		

Technical data

Code	SLI035073CCT_PW
Power	30/40/48 W
Nominal current	210 mA
Voltage	230 V
Energy consumption	48 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	6300 lm (360°)
Luminous flux**	3600/4800/5760 lm (360°)
Lamp efficacy	131 lm/W
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x35 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,

Logistics data

Bulk packaging	6 pcs.
Quantity per pallet	72 pcs.
Gross weight (1 pcs.)	1.4 kg

Related documents

 User manual Declaration of Conformity Photometric file

