

ALGINE BACKLIGHT CCT

SLI035073CCT_PW

LED luminaire ALGINE BACKLIGHT CCT with the possibility of changing the light color (CCT), with power regulation on the power supply (30 / 40 / 48 W), high light efficacy 131 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 3000 / 4000 / 6000K, we can adjust the light color depending on our needs and preferences. It is made of high-quality components, supported by a 5-year warranty. Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	30 / 40 / 48 W	Voltage	230 V
Luminous flux*	6300 lm (360°)	Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT	Beam angle	120 °
Degree of protection (IP)	IP20		

Technical data

Code	SLI035073CCT_PW
Power	30 / 40 / 48 W
Nominal current	210 mA
Voltage	230 V
Energy consumption	48 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	6300 lm (360°)
Luminous flux**	3600 / 4800 / 5760 lm (360°)
Lamp efficacy	131 lm/W
Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	5 years
Lifespan	50000 h
Housing material	Aluminum / Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x35 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,

Logistics data

Bulk packaging	6 pcs.
Quantity per pallet	72 pcs.
Gross weight (1 pcs.)	1.4 kg

Related documents

 User manual Declaration of Conformity Photometric file

