


PRODUCT DATASHEET

BLKH COMP RC V 8W ML 83040 BK

BULKHEAD COMPACT RECTANGULAR | Robust wall and ceiling luminaire with IP65 protection



VALUE
CLASS

Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Corridors, stairways, entrance areas
- Passages, underpasses
- Public areas

Product benefits

- Versatile due to selectable CCT in 3000K and 4000K
- Highly versatile due to selectable power steps (Power Select - PS) on the driver
- Suitable for use in dusty and damp locations thanks to high IP rating
- Suitable for use in public areas thanks to high IK rating
- Multiple mounting patterns for convenient installation

Product features

- Housing and cover made of UV-resistant PC
- Type of protection: IP65
- Impact resistance: IK10
- Luminous flux: up to 840 lm
- Lifetime (L70/B50) up to 50,000 h (at 25 °C)
- Ambient temperature in operation: -20...+45 °C
- Push wire terminal for tool-free connection
- Through-wiring possible



TECHNICAL DATA

Electrical data


Nominal wattage	8 W / 6 W / 4 W ¹⁾
Nominal voltage	220...240 V
Mains frequency	50/60 Hz
Nominal current	42...31...22 mA
Inrush current	4 A
Inrush current time T _{h50}	180 µs
Max. number of luminaires per miniature circuit breaker B16	104
Max. number of luminaires per miniature circuit breaker C10	87
Max. number of luminaires per miniature circuit breaker C16	140
Power factor λ	> 0.7
Total harmonic distortion	< 64 %
Protection class	II
Operating mode	Integrated LED driver

¹⁾ For possible options refer to lumen/power table image


Photometrical data

Luminous flux	840 lm / 690 lm / 500 lm ¹⁾
Luminous efficacy	105 lm/W / 115 lm/W / 125 lm/W ¹⁾
Color temperature	3000 K / 4000 K
Light color (designation)	Warm White / Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	5 sdcn
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	125 °


¹⁾ For possible options refer to lumen/power table image




BLKH COMP RC V 8W 830 IP65
BK



BLKH COMP RC V 8W 840 IP65
BK




BLKH COMP RC V 8W 830 IP65
BK



BLKH COMP RC V 8W 840 IP65
BK

Dimensions & Weight

Length	356.00 mm
Width	115.00 mm
Height	80.00 mm
Product weight	540.00 g



SF BLKH COMP RECTANGULAR

Materials & Colors

Product color	Black
Housing color	Black
RAL Color (most similar)	RAL 9005
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+45 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal
Type of protection	IP65
Protection class IK (shock resistance)	IK10
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Application environment	Outdoor
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	50000 h ¹⁾
Lifespan L80/B10 at 25 °C	40000 h ¹⁾
Lifespan L80/B50 at 25 °C	45000 h
Lifespan L90/B10 at 25 °C	20000 h
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	220...165...115 mA
ECG - Output ripple current	< 5 %

Certificates & Standards

Standards	CE / CB / UKCA / EAC / ENEC / TÜV SÜD
-----------	---------------------------------------

Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00052-V01.01-EN

Additional product data

Added function	MULTI SELECT
----------------	--------------

EQUIPMENT / ACCESSORIES

- Mounting screws and dowels included
- Anti-theft screw included

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	BULKHEAD COMPACT SEN
	Legal information	LSI BULKHEAD COMPACT
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	Legal Insert G11193421
	Legal information	Safety Insert G11230262
	Declarations of conformity	CE declaration_BLKH COMP RC V LUM
	Declarations of conformity UKCA	UKCA_BLKH COMP RC V LUM
	Certificates	ENEC BLKH COMP RC

Photometric and lighting design files		Document name
	IES file (IES)	BLKH COMP RC V 8W 830 IP65 BK
	IES file (IES)	BLKH COMP RC V 8W 840 IP65 BK
	LDT file (Eulumdat)	BLKH COMP RC V 8W 830 IP65 BK

Photometric and lighting design files		Document name
	LDT file (Eulumdat)	BLKH COMP RC V 8W 840 IP65 BK
	ULD file (DIALux)	BLKH COMP RC V 8W CPS IP65 BK
	ROLF file (RELUX)	BLKH COMP RC V 8W CPS IP65 BK
	UGR file (UGR table)	BLKH COMP RC V 8W 830 IP65 BK
	UGR file (UGR table)	BLKH COMP RC V 8W 840 IP65 BK
	Light distribution curve type cone	BLKH COMP RC V 8W 830 IP65 BK
	Light distribution curve type cone	BLKH COMP RC V 8W 840 IP65 BK
	Light distribution curve type polar	BLKH COMP RC V 8W 830 IP65 BK
	Light distribution curve type polar	BLKH COMP RC V 8W 840 IP65 BK
CAD/BIM files		Document name
	BIM Revit 3D	Bulkhead Compact Rectangular
	CAD STEP 3D	BLKH COMP
Tender texts		Document name
	Tender documents	BULKHEAD COMPACT RECTANGULAR RC V 8W CPS IP65 BK-EN


LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854290480	Folding box 1	85 mm x 128 mm x 390 mm	630.00 g	4.24 dm ³
4099854290497	Shipping box 6	400 mm x 400 mm x 200 mm	3780.00 g	32.00 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION

BLKH COMP RC						
W	8		6		4	
T	4000	3000	4000	3000	4000	3000
lm	840	800	690	660	500	500
lm/W	105	100	115	110	125	125



	B16	B10	C16	C10
BLKH COMP RC V 8W ML 83040 BK/WT	104	83	140	87
BLKH COMP RC V 8W ML 83040 BK/WT				

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.