

# ANDROMEDA

SLI033019WW\_PW

On track luminaire ANDROMEDA, with a power of 25 W, high light efficacy 128 lm/W. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Designed to be mounted on a track.



|                           |                       |                    |                 |
|---------------------------|-----------------------|--------------------|-----------------|
| Power                     | <b>25 W</b>           | Voltage            | <b>230 V</b>    |
| Luminous flux*            | <b>3200 lm (360°)</b> | Colour temperature | <b>3000 K</b>   |
| Colour of light           | <b>WW</b>             | Beam angle         | <b>36, 60 °</b> |
| Degree of protection (IP) | <b>IP20</b>           |                    |                 |

## Technical data

|                              |                   |
|------------------------------|-------------------|
| Code                         | SLI033019WW_PW    |
| Power                        | 25 W              |
| Nominal current              | 120 mA            |
| Voltage                      | 230 V             |
| Energy consumption           | 25 kWh/1000h      |
| Frequency                    | 50HZ Hz           |
| Protection class             | I                 |
| Power supply included        | +                 |
| Manufacturer of power supply | LIFUD             |
| Power factor                 | 0.9               |
| Useful luminous flux*        | 3200 lm (360°)    |
| Luminous flux**              | 2600 lm (360°)    |
| Lamp efficacy                | 128 lm/W          |
| Luminous intensity           | 6100 cd           |
| Colour temperature           | 3000 K            |
| Colour of light              | WW                |
| Beam angle                   | 36, 60 °          |
| RA                           | 80                |
| Light source included        | +                 |
| Producer of LED diodes       | SANAN             |
| Uniformity of color SDCM max | 5                 |
| Dimmable                     | No                |
| Working temperature range    | -20/+40 °         |
| Lifespan                     | 17000 h           |
| Housing material             | Aluminum, PLASTIC |
| Degree of protection (IP)    | IP20              |
| Colour                       | White             |
| Dimension (AxBxC)            | 170x160x74 mm     |
| For use                      | Inside            |
| Assembly method              | on track 3-fazowy |
| Application                  | INT               |
| Made in                      | PRC               |

## Logistics data

|                       |          |
|-----------------------|----------|
| Bulk packaging        | 24 pcs.  |
| Quantity per pallet   | 480 pcs. |
| Gross weight (1 pcs.) | 0.619 kg |

## Related documents

 User manual Declaration of Conformity Photometric file

