

ANDROMEDA PRIME

SLI033038CCT_PW

On track luminaire ANDROMEDA PRIME with the possibility of changing the light color (CCT), with a power of 16 W, high light efficacy 109 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 2700 / 4000 / 6000K, we can adjust the light color depending on our needs and preferences. Narrow beam angle 25° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.

CCT




Power	16 W	Voltage	230 V
Luminous flux*	1750 lm (360°)	Colour temperature	2700 / 4000 / 6000 K
Colour of light	CCT	Beam angle	25 °
Degree of protection (IP)	IP20		

Technical data

Code	SLI033038CCT_PW
Power	16 W
Nominal current	120 mA
Voltage	230 V
Energy consumption	16 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.5
Useful luminous flux*	1750 lm (360°)
Luminous flux**	1200 lm (360°)
Lamp efficacy	109 lm/W
Luminous intensity	5900 cd
Colour temperature	2700 / 4000 / 6000 K
Colour of light	CCT
Beam angle	25 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	2 years
Lifespan	17000 h
Housing material	Aluminum, PLASTIC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	63x134x184 mm
For use	Inside/Outside
Assembly method	on track 3-fazowy
Application	Inside
Made in	PRC
Other	Light color change function 2700K / 4000K / 6000K ,

Logistics data

Bulk packaging	40 pcs.
Quantity per pallet	880 pcs.
Gross weight (1 pcs.)	0.24 kg



Related documents

 User manual Declaration of Conformity Photometric file 3D model

