


ANDROMEDA

SLI033021WW_PW

LED luminaire ANDROMEDA, with power regulation on the power supply (15-27 W), high light efficacy 111 lm/W. The luminaire have an additional reflector (included with the luminaire) so that the lighting angle can be changed 36 or 60 degrees. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Designed to be mounted on a track.



Power **15-27 W**
Colour temperature **3000 K**
Beam angle **36, 60 °**

Voltage **230 V**
Colour of light **WW**
Degree of protection (IP) **IP20**

Technical data

Code	SLI033021WW_PW
Power	15-27 W
Nominal current	120 mA
Voltage	230 V
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	3000 lm (360°)
Luminous flux**	1500-2500 lm (360°)
Lamp efficacy	111 lm/W
Luminous intensity	6100 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	36, 60 °
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	Aluminum, PLASTIC
Degree of protection (IP)	IP20
Colour	Black
Dimension (AxBxC)	74x170x170 mm
For use	Inside
Assembly method	on track 3-fazowy
Application	Inside
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,

Logistics data

Bulk packaging	24 pcs.
Quantity per pallet	288 pcs.
Gross weight (1 pcs.)	0.59 kg



Related documents

 User manual Declaration of Conformity Photometric file 3D model

