

# ARTEMIDA MINI

SLI033023NW\_PW

LED luminaire ARTEMIDA MINI, with power regulation on the power supply (6,5-20 W), high light efficacy 115 lm/W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Designed to be mounted on a track.



|                    |                 |
|--------------------|-----------------|
| Power              | <b>6,5-20 W</b> |
| Colour temperature | <b>4000 K</b>   |
| Beam angle         | <b>36, 60 °</b> |

|                           |                      |
|---------------------------|----------------------|
| Voltage                   | <b>230 V</b>         |
| Colour of light           | <b>Neutral white</b> |
| Degree of protection (IP) | <b>IP20</b>          |

## Technical data

|                              |                                                 |
|------------------------------|-------------------------------------------------|
| Code                         | SLI033023NW_PW                                  |
| Power                        | 6,5-20 W                                        |
| Nominal current              | 90 mA                                           |
| Voltage                      | 230 V                                           |
| Energy consumption           | 20 kWh/1000h                                    |
| Frequency                    | 50HZ Hz                                         |
| Protection class             | II                                              |
| Power supply included        | Yes                                             |
| Power factor                 | 0.9                                             |
| Useful luminous flux*        | 2300 lm (360°)                                  |
| Luminous flux**              | 600-1700 lm (360°)                              |
| Lamp efficacy                | 115 lm/W                                        |
| Luminous intensity           | 3800 cd                                         |
| Colour temperature           | 4000 K                                          |
| Colour of light              | Neutral white                                   |
| Beam angle                   | 36, 60 °                                        |
| RA                           | >90                                             |
| Light source included        | Yes                                             |
| Uniformity of color SDCM max | 5                                               |
| Dimmable                     | No                                              |
| Working temperature range    | -20 / +40 °                                     |
| Warranty                     | 5 years                                         |
| Lifespan                     | 50000 h                                         |
| (On/Off)                     | 25000                                           |
| Housing material             | Aluminum, PLASTIC                               |
| Degree of protection (IP)    | IP20                                            |
| Colour                       | Black                                           |
| Dimension (AxBxC)            | 75x78x110 mm                                    |
| For use                      | Inside                                          |
| Assembly method              | on track 3-fazowy                               |
| Application                  | Inside                                          |
| Made in                      | PRC                                             |
| Other                        | DIP SWITCH - adjustable<br>power of luminaire , |

## Logistics data

|                       |          |
|-----------------------|----------|
| Bulk packaging        | 40 pcs.  |
| Quantity per pallet   | 480 pcs. |
| Gross weight (1 pcs.) | 0.56 kg  |

## Related documents

 User manual Declaration of Conformity Photometric file 3D model

