

ARTEMIDA MINI

SLI033024NW_PW

LED luminaire ARTEMIDA MINI, with power regulation on the power supply (6,5-20 W), high light efficacy 115 lm/W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Designed to be mounted on a track.



Power	6,5-20 W
Colour temperature	4000 K
Beam angle	36, 60 °

Voltage	230 V
Colour of light	Neutral white
Degree of protection (IP)	IP20

Technical data

Code	SLI033024NW_PW
Power	6,5-20 W
Nominal current	90 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	2300 lm (360°)
Luminous flux**	600-1700 lm (360°)
Lamp efficacy	115 lm/W
Luminous intensity	3800 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	36, 60 °
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	5 years
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	75x78x110 mm
For use	Inside
Assembly method	on track 3-fazowy
Application	Inside
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,

Logistics data

Bulk packaging	40 pcs.
Quantity per pallet	480 pcs.
Gross weight (1 pcs.)	0.36 kg

Related documents

 User manual Declaration of Conformity Photometric file 3D model

