

LED CANDLE

WQJ+14575

LED source LED CANDLE 1 W with E-14 base and in the shape of a glass 'candle'. It is characterised by a high light efficacy 110 lm/W. It is extremely economical to operate - their power output is 1 W. It is even more energy-efficient thanks to the use of durable COG filaments, which consume very little electricity. Wide beam angle 300° ensures even illumination of the room.



Power	1 W	Voltage	230 V
Luminous flux**	110 lm (360°)	Colour temperature	2700 K
Colour of light	WW	Beam angle	300 °
Socket	E14		

Technical data

Code	WQJ+14575
Power	1 W
Nominal current	10 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	1 kWh/1000h
Frequency	50HZ Hz
Power factor	0.4
Useful luminous flux*	110 lm (360°)
Luminous flux**	110 lm (360°)
Lamp efficacy	110 lm/W
Colour temperature	2700 K
Colour of light	WW
Beam angle	300 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	2 years
Lifespan	17000 h
Socket	E14
Dimension (AxBxC)	35x99 mm
For use	Inside
Application	INT
Made in	PRC

Logistics data

Bulk packaging	100 pcs.
Quantity per pallet	7000 pcs.
Gross weight (1 pcs.)	0.023 kg

Related documents



 Declaration of Conformity

