

LED CANDLE

WQJ+14575

LED source LED CANDLE 1 W with E-14 base and in the shape of a glass 'candle'. It is characterised by a high light efficacy 110 lm/W. It is extremely economical to operate - their power output is 1 W. It is even more energy-efficient thanks to the use of durable COG filaments, which consume very little electricity. Wide beam angle 300° ensures even illumination of the room.



Power	1 W	Voltage	230 V
Luminous flux**	110 lm (360°)	Colour temperature	2700 K
Colour of light	WW	Beam angle	300 °
Socket	E14		

Technical data

Code	WQJ+14575
Power	1 W
Nominal current	10 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	1 kWh/1000h
Frequency	50HZ Hz
Power factor	0.4
Useful luminous flux*	110 lm (360°)
Luminous flux**	110 lm (360°)
Lamp efficacy	110 lm/W
Colour temperature	2700 K
Colour of light	WW
Beam angle	300 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Socket	E14
Dimension (AxBxC)	35x99 mm
For use	Inside
Application	INT
Made in	PRC

Related documents



 Declaration of Conformity

