

LED G4

W0J+13784

LED source LED G4 1,2 W. It is perfect for use in households, hotels, shops, or restaurants as decorative or accent lighting, and can be installed in luminaires that have a G4 base.. It is characterised by a high light efficacy 133 lm/W. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier



Power	1,2 W
Luminous flux**	160 lm (360°)
Colour of light	WW
Socket	G4

Voltage	12 V
Colour temperature	3000 K
Beam angle	120 °

Technical data

Code	WQJ+13784
Power	1,2 W
Nominal current	110 mA
Voltage	12 V
Energy efficiency class	D
Energy consumption	2 kWh/1000h
Frequency	0-50HZ Hz
Power factor	0.4
Useful luminous flux*	160 lm (120°)
Luminous flux**	160 lm (360°)
Lamp efficacy	133 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	2 years
Lifespan	17000 h
(On/Off)	15000
Socket	G4
Dimension (AxBxC)	ø20x30x8 mm
For use	Inside
Application	INT
Made in	PRC

Logistics data

Bulk packaging	500 pcs.
Quantity per pallet	18000 pcs.
Gross weight (1 pcs.)	0.007 kg

Related documents



 Declaration of Conformity

