


LED G4

WOJ+13782

LED source LED G4 2 W. It is perfect for use in households, hotels, shops, or restaurants as decorative or accent lighting, and can be installed in luminaires that have a G4 base.. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier



Power	2 W	Voltage	12 V
Luminous flux**	190 lm (360°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	120 °
Socket	G4		

Technical data

Code	WQJ+13782
Power	2 W
Nominal current	240 mA
Voltage	12 V
Energy efficiency class	F
Energy consumption	2 kWh/1000h
Frequency	0-50HZ Hz
Power factor	0.5
Useful luminous flux*	190 lm (120°)
Luminous flux**	190 lm (360°)
Lamp efficacy	95 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	2 years
Lifespan	17000 h
Socket	G4
Dimension (AxBxC)	30x42x8 mm
For use	Inside
Application	INT
Made in	PRC

Logistics data

Bulk packaging	500 pcs.
Quantity per pallet	18000 pcs.
Gross weight (1 pcs.)	0.007 kg

Related documents



 Declaration of Conformity

