


# LED G4

W0J+14432

LED source LED G4 2,5 W. It is perfect for use in households, hotels, shops, or restaurants as decorative or accent lighting, and can be installed in luminaires that have a G4 base.. It is characterised by a high light efficacy 116 lm/W. It is made of high-quality components, supported by a 5-year warranty. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Wide beam angle 270° ensures even illumination of the room.



|                 |                      |
|-----------------|----------------------|
| Power           | <b>2,5 W</b>         |
| Luminous flux** | <b>290 lm (360°)</b> |
| Colour of light | <b>CW</b>            |
| Socket          | <b>G4</b>            |

|                    |               |
|--------------------|---------------|
| Voltage            | <b>12 V</b>   |
| Colour temperature | <b>6000 K</b> |
| Beam angle         | <b>270 °</b>  |

## Technical data

|                              |               |
|------------------------------|---------------|
| Code                         | WQJ+14432     |
| Power                        | 2,5 W         |
| Nominal current              | 300 mA        |
| Voltage                      | 12 V          |
| Energy efficiency class      | F             |
| Energy consumption           | 3 kWh/1000h   |
| Frequency                    | 50HZ Hz       |
| Useful luminous flux*        | 290 lm (360°) |
| Luminous flux**              | 290 lm (360°) |
| Lamp efficacy                | 116 lm/W      |
| Colour temperature           | 6000 K        |
| Colour of light              | CW            |
| Beam angle                   | 270 °         |
| RA                           | 80            |
| Uniformity of color SDCM max | 5             |
| Dimmable                     | No            |
| Working temperature range    | -20 / +40 °   |
| Warranty                     | 5 years       |
| Lifespan                     | 50000 h       |
| (On/Off)                     | 25000         |
| Socket                       | G4            |
| Dimension (AxBxC)            | ø13x45 mm     |
| For use                      | N/A           |
| Made in                      | PRC           |

## Logistics data

|                       |            |
|-----------------------|------------|
| Bulk packaging        | 1440 pcs.  |
| Quantity per pallet   | 25920 pcs. |
| Gross weight (1 pcs.) | 0.0065 kg  |

## Related documents



 Declaration of Conformity