

LED G4

W0J+14432

LED source LED G4 2,5 W. It is perfect for use in households, hotels, shops, or restaurants as decorative or accent lighting, and can be installed in luminaires that have a G4 base.. It is characterised by a high light efficacy 116 lm/W. It is made of high-quality components, supported by a 5-year warranty. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Wide beam angle 270° ensures even illumination of the room.



Power	2,5 W	Voltage	12 V
Luminous flux**	290 lm (360°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	270 °
Socket	G4		

Technical data

Code	WQJ+14432
Power	2,5 W
Nominal current	300 mA
Voltage	12 V
Energy efficiency class	F
Energy consumption	3 kWh/1000h
Frequency	50HZ Hz
Useful luminous flux*	290 lm (360°)
Luminous flux**	290 lm (360°)
Lamp efficacy	116 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	270 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Socket	G4
Dimension (AxBxC)	ø13x45 mm
For use	N,A
Made in	PRC

Logistics data

Bulk packaging	1440 pcs.
Quantity per pallet	25920 pcs.
Gross weight (1 pcs.)	0.0065 kg

Related documents



 Declaration of Conformity