


LED G4

WOJ+14430

LED source LED G4 2,5 W. It is perfect for use in households, hotels, shops, or restaurants as decorative or accent lighting, and can be installed in luminaires that have a G4 base.. It is characterised by a high light efficacy 108 lm/W. It is made of high-quality components, supported by a 5-year warranty. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Wide beam angle 270° ensures even illumination of the room.



Power	2,5 W
Luminous flux**	270 lm (360°)
Colour of light	WW
Socket	G4

Voltage	12 V
Colour temperature	3000 K
Beam angle	270 °

Technical data

Code	WQJ+14430
Power	2,5 W
Nominal current	300 mA
Voltage	12 V
Energy efficiency class	F
Energy consumption	3 kWh/1000h
Frequency	50HZ Hz
Useful luminous flux*	270 lm (360°)
Luminous flux**	270 lm (360°)
Lamp efficacy	108 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	270 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Socket	G4
Dimension (AxBxC)	ø13x45 mm
For use	N/A
Made in	PRC

Logistics data

Bulk packaging	1440 pcs.
Quantity per pallet	25920 pcs.
Gross weight (1 pcs.)	0.0065 kg

Related documents



 Declaration of Conformity