

LED G4

WOJ+13117

LED source LED G4 1,5 W in silicone cover. It is perfect for use in households, hotels, shops, or restaurants as decorative or accent lighting, and can be installed in luminaires that have a G4 base.. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Wide beam angle 270° ensures even illumination of the room.



Power	1,5 W	Voltage	12 V
Luminous flux**	95 lm (360°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	270 °
Socket	G4		

Technical data

Code	WQJ+13117
Power	1,5 W
Nominal current	80 mA
Voltage	12 V
Energy efficiency class	G
Energy consumption	2 kWh/1000h
Frequency	50HZ Hz
Power factor	0,4
Useful luminous flux*	95 lm (360°)
Luminous flux**	95 lm (360°)
Lamp efficacy	63 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	270 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Socket	G4
Dimension (AxBxC)	79,5x36 mm
For use	Inside
Application	INT
Made in	PRC

Logistics data

Bulk packaging	500 pcs.
Quantity per pallet	18000 pcs.
Gross weight (1 pcs.)	0.0067 kg

Related documents



 Declaration of Conformity

