

LED GLS

WQJ+13876

LED source LED GLS 4 W with E-27 base and in the shape of a traditional glass bulb. It is characterised by a high light efficacy 113 lm/W. It is even more energy-efficient thanks to the use of durable COG filaments, which consume very little electricity. Wide beam angle 300° ensures even illumination of the room.



Power	4 W	Voltage	230 V
Luminous flux**	450 lm (360°)	Colour temperature	2700 K
Colour of light	WW	Beam angle	300 °
Socket	E27		

Technical data

Code	WQJ+13876
Power	4 W
Nominal current	30 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	4 kWh/1000h
Frequency	50HZ Hz
Power factor	0.5
Useful luminous flux*	450 lm (360°)
Luminous flux**	450 lm (360°)
Lamp efficacy	113 lm/W
Colour temperature	2700 K
Colour of light	WW
Beam angle	300 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	2 years
Lifespan	17000 h
(On/Off)	15000
Socket	E27
Dimension (AxBxC)	60X107 mm
For use	Inside
Application	INT
Made in	PRC

Logistics data

Bulk packaging	100 pcs.
Quantity per pallet	2500 pcs.
Gross weight (1 pcs.)	0.064 kg

Related documents



 Declaration of Conformity



 Photometric file

