

NOCTIS LUX 3

SLI029050NW_PW

Floodlight NOCTIS LUX 3, with a power of 30 W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK07 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Designed for surface mounting.



Power	30 W	Voltage	230 V
Luminous flux*	2800 lm (120°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	100 °
IK	07	Degree of protection (IP)	IP65

Technical data

Code	SLI029050NW_PW
Power	30 W
Nominal current	130 mA
Voltage	230 V
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	2800 lm (120°)
Luminous flux**	2800 lm (360°)
Lamp efficacy	93 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	2 years
Lifespan	17000 h
(On/Off)	15000
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	150x110x27 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC

Logistics data

Bulk packaging	20 pcs.
Quantity per pallet	840 pcs.
Gross weight (1 pcs.)	0.386 kg



Related documents



 Declaration of Conformity



 Photometric file

