

NOCTIS MAX

SLI029056CW_PW

Floodlight NOCTIS MAX, with a power of 100 W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK08 class provides impact resistance. Narrow beam angle 85° gives directional light so that selected surfaces can be better exposed. Designed for surface mounting.



Power	100 W	Voltage	230 V
Luminous flux*	8600 lm (120°)	Colour temperature	6500 K
Colour of light	CW	Beam angle	85 °
IK	08	Degree of protection (IP)	IP65

Technical data

Code	SLI029056CW_PW
Power	100 W
Nominal current	430 mA
Voltage	230 V
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.99
Useful luminous flux*	8600 lm (120°)
Luminous flux**	8600 lm (360°)
Lamp efficacy	86 lm/W
Luminous intensity	5100 cd
Colour temperature	6500 K
Colour of light	CW
Beam angle	85 °
RA	>80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Warranty	5 years
Lifespan	50000 h
Housing material	Aluminum+PC LENS
IK	08
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	294x215x30 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC

Logistics data

Bulk packaging	20 pcs.
Quantity per pallet	300 pcs.
Gross weight (1 pcs.)	1.055 kg



Related documents

 User manual Declaration of Conformity Photometric file

