

NOCTIS MAX

SLI029058CW_PW

Floodlight NOCTIS MAX, with a power of 150 W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK08 class provides impact resistance. Narrow beam angle 85° gives directional light so that selected surfaces can be better exposed. Designed for surface mounting.



IP65

IK08



Power	150 W	Voltage	230 V
Luminous flux*	14000 lm (120°)	Colour temperature	6500 K
Colour of light	CW	Beam angle	85 °
IK	08	Degree of protection (IP)	IP65

Technical data

Code	SLI029058CW_PW
Power	150 W
Nominal current	655 mA
Voltage	230 V
Energy consumption	150 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.99
Useful luminous flux*	14000 lm (120°)
Luminous flux**	14000 lm (360°)
Lamp efficacy	93 lm/W
Luminous intensity	7800 cd
Colour temperature	6500 K
Colour of light	CW
Beam angle	85 °
RA	>80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Warranty	5 years
Lifespan	50000 h
Housing material	Aluminum+PC LENS
IK	08
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	360x262x30 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC

Logistics data

Bulk packaging	10 pcs.
Quantity per pallet	160 pcs.
Gross weight (1 pcs.)	1.69 kg



Related documents

 User manual Declaration of Conformity Photometric file

