

NOCTIS MAX

SLI029057NW_PW

Floodlight NOCTIS MAX, with a power of 200 W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK10 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Narrow beam angle 85° gives directional light so that selected surfaces can be better exposed. Designed for surface mounting.



Power	200 W	Voltage	230 V
Luminous flux*	17500 lm (120°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	85 °
IK	10	Degree of protection (IP)	IP65

Technical data

Code	SLI029057NW_PW
Power	200 W
Nominal current	850 mA
Voltage	230 V
Energy consumption	200 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.99
Useful luminous flux*	17500 lm (120°)
Luminous flux**	17500 lm (360°)
Lamp efficacy	88 lm/W
Luminous intensity	10500 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	85 °
RA	>80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	Aluminum+PC LENS
IK	10
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	410x290x30 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



Related documents



 User manual



 Declaration of Conformity



 Photometric file

