

NYMPHEA CITY PRO 2

SLI031039CCT_PW_SENSOR

Plafond NYMPHEA CITY PRO 2 with the possibility of changing the light color (CCT), with power regulation on the power supply (18 / 24 W), high light efficacy 145 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 3000 / 4000 / 6000K, we can adjust the light color depending on our needs and preferences. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK08 class provides impact resistance. Designed for surface mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

**CCT****IP65****IK08**

Power	18 / 24 W	Voltage	230 V
Luminous flux*	3500 lm (360°)	Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT	Beam angle	120 °
IK	08	Degree of protection (IP)	IP65

Technical data

Code	SLI031039CCT_PW_SENSOR
Power	18 / 24 W
Nominal current	170 mA
Voltage	230 V
Energy consumption	24 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.65
Useful luminous flux*	3500 lm (360°)
Luminous flux**	1800 / 2400 lm (360°)
Lamp efficacy	145 lm/W
Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT
Beam angle	120 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	5 years
Lifespan	50000 h
Housing material	PC
IK	08
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	320x80 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT / EXT
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,

Logistics data

Bulk packaging	8 pcs.
Quantity per pallet	96 pcs.
Gross weight (1 pcs.)	1.08 kg

Related documents

 User manual Declaration of Conformity

