

ORBITO

SLI043018NW_PW

Downlight luminaire ORBITO, with a power of 10 W, high light efficacy 120 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a high IP44 rating, making it ideal for use in rooms with high humidity. It also stands out for its very high colour rendering index RA>90. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Narrow beam angle 40° gives directional light so that selected objects or surfaces can be better exposed. Designed for recessed mounting.



Power	10 W	Voltage	230 V
Colour temperature	4000 K	Colour of light	Neutral white
Beam angle	40 °	UGR	<19
IK	06	Degree of protection (IP)	IP44

Technical data

Code	SLI043018NW_PW
Power	10 W
Nominal current	50 mA
Voltage	230 V
Energy consumption	10 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	1200 lm (360°)
Luminous flux**	950 lm (360°)
Lamp efficacy	120 lm/W
Luminous intensity	1800 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	40 °
UGR	<19
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	5 years
Lifespan	50000 h
Housing material	Aluminum
IK	06
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	97x65 mm
Mounting hole	75 mm
For use	Inside
Assembly method	Recessed
Application	Inside
Made in	PRC

Logistics data

Bulk packaging	30 pcs.
Quantity per pallet	720 pcs.
Gross weight (1 pcs.)	0.35 kg

Related documents

 User manual Declaration of Conformity Photometric file 3D model

