

# VIGA

SLI045005CW\_PW

Linear luminaire VIGA, with a power of 14 W, high light efficacy 121 lm/W. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Suitable for both surface and suspended mounting.



|                           |                       |                    |               |
|---------------------------|-----------------------|--------------------|---------------|
| Power                     | <b>14 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux*            | <b>1700 lm (360°)</b> | Colour temperature | <b>6000 K</b> |
| Colour of light           | <b>CW</b>             | Beam angle         | <b>120 °</b>  |
| Degree of protection (IP) | <b>IP20</b>           |                    |               |

## Technical data

|                              |                           |
|------------------------------|---------------------------|
| Code                         | SLI045005CW_PW            |
| Power                        | 14 W                      |
| Nominal current              | 105 mA                    |
| Voltage                      | 230 V                     |
| Energy consumption           | 14 kWh/1000h              |
| Frequency                    | 50HZ Hz                   |
| Protection class             | II                        |
| Power factor                 | 0.5                       |
| Useful luminous flux*        | 1700 lm (360°)            |
| Luminous flux**              | 1500 lm (360°)            |
| Lamp efficacy                | 121 lm/W                  |
| Colour temperature           | 6000 K                    |
| Colour of light              | CW                        |
| Beam angle                   | 120 °                     |
| RA                           | 80                        |
| Uniformity of color SDCM max | 5                         |
| Dimmable                     | No                        |
| Working temperature range    | -20 / +40 °               |
| Warranty                     | 2 years                   |
| Lifespan                     | 17000 h                   |
| (On/Off)                     | 15000                     |
| Housing material             | PC                        |
| Degree of protection (IP)    | IP20                      |
| Colour                       | White                     |
| Dimension (AxBxC)            | 76x580x26 mm              |
| For use                      | Inside                    |
| Assembly method              | On the ceiling, Suspended |
| Application                  | Inside                    |
| Made in                      | PRC                       |

## Logistics data

|                       |           |
|-----------------------|-----------|
| Bulk packaging        | 50 pcs.   |
| Quantity per pallet   | 1000 pcs. |
| Gross weight (1 pcs.) | 0.19 kg   |

## Related documents

 User manual Declaration of Conformity Photometric file

