

VIGA

SLI045004WW_PW

Linear luminaire VIGA, with a power of 28 W, high light efficacy 114 lm/W. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Suitable for both surface and suspended mounting.



Power	28 W	Voltage	230 V
Luminous flux*	3200 lm (360°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	120 °
Degree of protection (IP)	IP20		

Technical data

Code	SLI045004WW_PW
Power	28 W
Nominal current	140 mA
Voltage	230 V
Energy consumption	28 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	3200 lm (360°)
Luminous flux**	2600 lm (360°)
Lamp efficacy	114 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	2 years
Lifespan	17000 h
(On/Off)	15000
Housing material	PC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	76x1200x26 mm
For use	Inside
Assembly method	On the ceiling, Suspended
Application	INT
Made in	PRC

Logistics data

Bulk packaging	25 pcs.
Quantity per pallet	325 pcs.
Gross weight (1 pcs.)	0.31 kg

Related documents

 Declaration of Conformity Photometric file

