


VIGA

SLI045007CW_PW

Linear luminaire VIGA, with a power of 20 W, high light efficacy 120 lm/W. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Suitable for both surface and suspended mounting.



Power	20 W
Luminous flux*	2400 lm (360°)
Colour of light	CW
Degree of protection (IP)	IP20

Voltage	230 V
Colour temperature	6000 K
Beam angle	120 °

Technical data

Code	SLI045007CW_PW
Power	20 W
Nominal current	150 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.6
Useful luminous flux*	2400 lm (360°)
Luminous flux**	2000 lm (360°)
Lamp efficacy	120 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	2 years
Lifespan	17000 h
(On/Off)	15000
Housing material	PC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	76x900x26 mm
For use	Inside
Assembly method	On the ceiling, Suspended
Application	Inside
Made in	PRC

Logistics data

Bulk packaging	50 pcs.
Quantity per pallet	350 pcs.
Gross weight (1 pcs.)	0.3 kg

Related documents

 User manual Declaration of Conformity Photometric file

