


VIGA

SLI045008CW_PW

Linear luminaire VIGA, with a power of 35 W, high light efficacy 126 lm/W. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Suitable for both surface and suspended mounting.



Power	35 W	Voltage	230 V
Luminous flux*	4400 lm (360°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	120 °
Degree of protection (IP)	IP20		

Technical data

Code	SLI045008CW_PW
Power	35 W
Nominal current	165 mA
Voltage	230 V
Energy consumption	35 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.95
Useful luminous flux*	4400 lm (360°)
Luminous flux**	3600 lm (360°)
Lamp efficacy	126 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	2 years
Lifespan	17000 h
(On/Off)	15000
Housing material	PC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	76x1500x26 mm
For use	Inside
Assembly method	On the ceiling, Suspended
Application	Inside
Made in	PRC

Logistics data

Bulk packaging	25 pcs.
Quantity per pallet	325 pcs.
Gross weight (1 pcs.)	0.42 kg

Related documents

 User manual Declaration of Conformity Photometric file

